



25-06 Remington

with **Boron Nitride Coated**
120-grain DeepCurl® SP

0.257"	DeepCurl SP
Weight, grains	120
Case	Federal®
Primer	CCI 200, 250*
COAL	3.150"
Speer Part No.	1416

Propellant	START CHARGE		MAXIMUM CHARGE	
	Weight, grs	Muzzle Velocity, ft/sec	Weight, grs	Muzzle Velocity, ft/sec
RE 25	53.0	2,849	57.0	3,045
RE 22	51.0	2,871	54.0	3,032
4000-MR*	46.5	2,789	50.5	3,019
IMR 7828	51.2	2,790	55.2	3,019
H4831SC	47.5	2,766	51.5	2,958
H414	42.0	2,667	46.0	2,888

WARNING: DO NOT USE BORON NITRIDE COATED BULLET DATA FOR UNCOATED BULLETS.

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current Speer® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As ATK has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum Loads should be used with CAUTION • C = Compressed Load • *Magnum Primer used with this powder.*