



## 280 Remington with 160-grain DeepCurl™

<b>0.284"</b>	<b>DeepCurl</b>
Weight, grains	160
Case	Federal®
Primer	Fed 210, Fed 215*
COAL	3.230"
Speer Part No.	1639

Propellant	START CHARGE		MAXIMUM CHARGE	
	Weight, grs	Muzzle Velocity, ft/sec	Weight, grs	Muzzle Velocity, ft/sec
Reloder 22	53.0	2615	<b>57.0</b>	2805
Reloder 19	51.0	2579	<b>55.0</b>	2766
IMR 4831	49.0	2547	<b>53.0</b>	2761
AA 3100	51.0	2547	<b>55.0</b>	2759
IMR 4350	48.0	2521	<b>52.0</b>	2752
H1000	57.0	2581	<b>61.0C</b>	2745
Hunter*	48.0	2568	<b>52.0</b>	2737
H4831SC	52.0	2559	<b>56.0</b>	2731
760*	45.0	2478	<b>49.0</b>	2664

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current Speer® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As ATK has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum Loads should be used with CAUTION • C = Compressed Load • \*Magnum Primer used with this powder.*