



# 30-06 Springfield

with 180-grain DeepCurl™

<b>0.308"</b>	<b>DeepCurl</b>
Weight, grains	180
Case	Federal®
Primer	Fed 210, Fed 215*
COAL	3.180"
Speer Part No.	2043

Propellant	START CHARGE		MAXIMUM CHARGE	
	Weight, grs	Muzzle Velocity, ft/sec	Weight, grs	Muzzle Velocity, ft/sec
Reloder 19	55.0	2550	<b>59.0C</b>	2735
Ramshot Hunter*	53.0	2580	<b>57.0C</b>	2716
IMR 4350	51.0	2506	<b>55.0C</b>	2682
IMR 4841	52.0	2492	<b>56.0C</b>	2681
AA 3100	53.0	2474	<b>57.0C</b>	2680
760*	49.0	2467	<b>53.0</b>	2654
H414*	50.0	2543	<b>52.0</b>	2648
AA 4350	52.0	2480	<b>56.0C</b>	2644
Reloder 22	55.0	2491	<b>59.0C</b>	2637
H4831SC	55.0	2485	<b>59.0C</b>	2628

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current Speer® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As ATK has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum Loads should be used with CAUTION • C = Compressed Load • \*Magnum Primer used with this powder.*